



Technical Data Sheet



TP-213 S1P BRN/ **MODEL Y S1P BROWN**

Model Description:

Leather shoe, Beige mesh lining, Puncture resistant steel plate, Shock resistant, Steel toe, S1P, DDPU sole.

Specifications:

Upper	Genuine Leather (Barton Print)
Lining	Beige Mesh
Insole	Foam Footbed
Outsole	PU/PU
Toecap	Steel Toe
Midsole	Steel Plate
Safety Standards	S1P, EN ISO 20345:2021
Size Range	EU 38-46
Shoe weight	712 grams (approx.)

- 200 JOULE
TOECAP
- SLIP
RESISTANT
- SHOCK
ABSORPTION
- ANTI-STATIC
- PETROL AND
CHEMICAL
RESISTANT
- ANTI-NAIL
MIDSOLE
- OIL
RESISTANT



Oil and Fuel Resistant
The outsole is resistant against oil and fuel.



Steel Toecap
The feet of the wearer against falling or rolling objects.



Steel Midsole
Puncture resistant steel midsoles are made from stainless or coated steel and prevent sharp objects from penetrating the outsole.



Breathable Leather Upper
High degree of wearer comfort combined with durability in versatile applications.

Industries:

Automotive, Chemical, Cleaning, Construction, Logistics, Metal Fabrication, Oil & Gas, Other Industries.

Environments:

Dry environment, Muddy environment, Uneven surfaces, Wet environment.

Maintenance Instructions:

To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

Description			Measure Unit	Result	EN345 required
Complete shoe	Protection of toes: metal tip resistant to: A shock of 200J Pressure of 1500 kg Sole: Metal plate resistant to 1100N	Impact resistance (Clearance after shock) Compressive strength (after clearance compression)	Mm	>15	>14
			Mm		14
	Anti-shock system: Low-Density polyurethane and profile of the heel	Shock absorption in heel	J	>35	>20
Upper	Leather, black	Permeability to water vapor	Mg/m2 hour	>2,0	>0,8
	Thickness 1,6mm	Permeability coefficient	Mg/cm2	>25,6	>20
Front	Thickness 1,2mm	Permeability coefficient	Mg/cm2	>35	>30
Lining	Mesh Beige	Permeability to water vapor	Mg/cm2 hour	>2,1	>2
Back	Thickness 1,2mm	Permeability coefficient	Mg/cm2	>45	>30
Insole	Absorbent, resistant to abrasion and to exfoliation	Abrasion resistance	Cycles	>400	>400
Outsole	Single density polyurethane injected directly onto the upper	Abrasion resistance (volume loss)	Mm3	110	<150
	Shock absorption, abrasion resistant, mineral oils and weak acids	Oil resistance (volume variation AV)	%	8,0-9.0	<+12
		Coefficient of adhesion of the outsole	-	0,04	>0,15

Sample size: 42

Our shoes are constantly evolving, the technical data above may change. All product names and brand Lancer®, are registered and may not be used or reproduced in any format, without written consent from us.