



Technical Data Sheet



TP-222L SBP/ **MODEL 3 SBP**

Model Description:

Leather shoe, Grey mesh lining, Puncture resistant steel plate, Shock resistant, Steel toe, SBP, DDPU sole.

Specifications:

Upper	Genuine Leather (Barton Print)
Lining	Grey Mesh
Insole	Foam Footbed
Outsole	PU/PU
Toecap	Steel Toe
Midsole	Steel Plate
Safety Standards	SBP, EN ISO 20345:2021
Size Range	EU 38-46
Shoe weight	438 grams (approx.)



200 JOULE
TOECAP



SLIP
RESISTANT



SHOCK
ABSORPTION



ANTI-STATIC



PETROL AND
CHEMICAL
RESISTANT



ANTI-NAIL
MIDSOLE



OIL
RESISTANT



Oil and Fuel Resistant

The outsole is resistant against oil and fuel.



Steel Toecap

The feet of the wearer against falling or rolling objects.



Steel Midsole

Puncture resistant steel midsoles are made from stainless or coated steel and prevent sharp objects from penetrating the outsole.



Breathable Leather Upper

High degree of wearer comfort combined with durability in versatile applications.

Industries:

Automotive, Chemical, Cleaning, Construction, Logistics, Metal Fabrication, Oil & Gas, Other Industries.

Environments:

Dry environment, Muddy environment, Uneven surfaces, Wet environment.

Maintenance Instructions:

To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

Description			Measure Unit	Result	EN345 required
Complete shoe	Protection of toes: metal tip resistant to: A shock of less than 80J Pressure of 50 kg Sole: Metal plate resistant to 500N	Impact resistance (Clearance after shock) Compressive strength (after clearance compression)	Mm	>15	>14
			Mm		14
	Anti-shock system: Low-Density polyurethane and profile of the heel	Shock absorption in heel	J	>35	>20
Upper	Leather, black	Permeability to water vapor	Mg/m2 hour	>2,0	>0,8
	Thickness 1,6mm	Permeability coefficient	Mg/cm2	>25,6	>20
Front	Thickness 1,2mm	Permeability coefficient	Mg/cm2	>35	>30
Lining	Nylon mesh grey	Permeability to water vapor	Mg/cm2 hour	>2,1	>2
Back	Thickness 1,2mm	Permeability coefficient	Mg/cm2	>45	>30
Insole	absorbent, resistant to abrasion and to exfoliation	Abrasion resistance	Cycles	>400	>400
Outsole	Single density polyurethane injected directly onto the upper	Abrasion resistance (volume loss)	Mm3	110	<150
	Shock absorption, abrasion resistant, mineral oils and weak acids	Oil resistance (volume variation AV)	%	8,0-9,0	<+12
		Coefficient of adhesion of the outsole	-	0,04	>0,15

Sample size: 42

Our shoes are constantly evolving, the technical data above may change. All product names and brand Lancer®, are registered and may not be used or reproduced in any format, without written consent from us.